



frontmost panel
when folded

Auto Shocker™ INSTRUCTIONS

For use in cars, trucks or SUV's with interiors of up to 250 cubic feet.

Read all instructions before using!


In order to guarantee success, follow all directions **exactly as indicated**

1. Place vehicle out of direct sunlight (ie. Carport or garage) sunlight/UV rays weakens Chlorine Dioxide strength.
2. Open container and remove all contents
3. Read all information on foil packet then open packet at notch edge carefully so as to not damage content inside. Remove the CLO2DMG Technology™ pouch from inside and discard desiccant.
4. Take the CLO2DMG Technology™ pouch and shake thoroughly to help loosen and mix ingredients. Then place pouch back in



the container provided.

5. Place container inside vehicle in a cup holder or on a stable flat surface on top of lid provided. **Do not put directly onto carpet. Do not apply when carpet is wet.**
6. Using measuring cup provided add one full measuring cup of warm tap water over pouch to activate. **Do not put lid back on container** until treatment is over and product is ready to be discarded.
7. Close all doors and windows and lock vehicle to prevent others from entering vehicle while the product is working. **This product is completely nontoxic however it is an irritant, therefore there should be no persons or pets in the vehicle while the Auto Shocker™ is activated and in use.**
8. Leave the Auto Shocker™ working for 4 to 24 hours depending on severity of odor.
9. At end of treatment open all doors for ventilation, and place lid back on the Auto Shocker™ and dispose in an outdoors



SPECIAL INSTRUCTIONS: Fold in half lengthwise then in accordion style (aka broadside accordion). The contact info must appear on the back of finished folded piece.

waste container.

10. Allow vehicle to ventilate for 20 minutes before entering.

TIPS: In order to ensure optimal performance, you may want to follow these tips.

- a. Before using Auto Shocker™, make sure all interior compartments are open (ie. Glove box, armrest compartments, etc.).
- b. Pull down all visors.
- c. Place floor mats on their sides.
- d. Clean out ashtrays and remove trash.
- e. Change air filters.
- f. Before step 9, set fan to recycle and run fan for 15 minutes.
- g. Minimum temperature for Auto Shocker™ to work most effectively must not be below 50 degrees Fahrenheit.

For money back guarantee policy please hold onto foil packet and refer to our FAQ on our website.

— crop marks
..... fold marks

Auto Shocker™ is a safe and non-toxic product that will degrade into a saltwater solution. All components are biodegradable and eco-friendly. Made in the USA.

1-877-RX BIOCIDE / 1-877-792-4624
www.BiocideSystems.com

WARNING: Make sure to place lid on container before removing to avoid spilling any excess liquids as this may bleach some surfaces it comes in contact with.

AUS-RT-01-040213

■ Cyan [4CP] ■ PMS 369 [4CP]
■ PMS 186 [4CP] ■ Cool Gray 8 [4CP]



backmost panel
when folded

